

www.equip-info.net



Features

- Easily mount into 3.5" drive bay, powered by USB port (DC + 5V)
- Includes beige, black and silver color bezel for swapping.
- Supported SM/xD, SD/MMC, MS and CF/MD memory slots.
- Allows direct data transfer between different types of memory cards.
- Mini size, suitable for all desktop PC enclosure.
- USB 2.0 high-speed data transfer rate up to 480Mbps.
- Fully backward compatible with USB 1.1 devices.
- Two LED indicators for in-use status.
- All media slots can be used at the same for data exchange.
- 1x USB 2.0 downstream port for convenient access.

Package Contents

1 x 3.5" Int. Card Reader

1 x User Manual (G/E)

3 x Color Bezels

Set of screws

USB 2.0 Card Reader int. 3.5" + USB port

Universal | 128578 | Page 1/2

Memory Cards Supported

- SD, MMC I/II, MMC 4.0, MMC Dual Voltage, RS MMC, RS MMC Dual Voltage, RS MMC 4.0, xD, xD (M), xD (H)
- MS, MS Pro, MS Magic Gate, MS-Pro Magic Gate, HS-MS-Pro Magic Gate, MS-Duo, MS Pro-Duo, MS Pro-Duo PSP, MS Pro-Duo Gaming, HS-MS-Pro Duo, MS-Duo Magic Gate, MS Pro-Duo Magic Gate, CF I/II, CF Ultra II, CF Extreme III

Maximum Capacity of Memory Card Supported

SD: 16GBSDHC: 32GBMMC: 16GBMS: 16GBCF: 32GBxD: 2GB





www.equip-info.net



USB 2.0 Card Reader int. 3.5" + USB port

Universal | 128578 | Page 2/2

Specifications

LED Indicator	Power-on LED
	Memory card in-use LED
Bus Interface	USB 2.0 or 1.1
Power Supply	5V by USB Port
Operating	0 ~ 50°C
Temperature	
Storage	-10 ~ 60°C
Temperature	
Cable	USB 2.0 Cable, 60cm length
Dimensions	119(L)*102.1(W)*25.4(H) mm
Weight	230g
Certification	FCC Class B, CE
OS Supported	Windows 98/SE/ME
	Windows 2000, 2003 Server
	Windows XP/Vista 32/64-bit
	Windows 7
	Mac OS9.2 or Higher
	Linux OS 2.4.X or Higher

